


1LExtra light load
Extra leichte Last**CARICO EXTRA LEGGERO**

	R	XLL 35%		Max 50%		L₀
	R	S₁	F₁	S₂	F₂	
Codice Ctg. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 10 (d) Spina • Rod Ø mm 5						
Sezione filo • Wire section 2,1 x 0,9						
1L10025	8,5	8,8	74	12,5	106	25
1L10032	6,5	11,2	73	16,0	104	32
1L10038	5,5	13,3	73	19,0	105	38
1L10045	5,0	15,4	77	22,0	110	44
1L10050	4,5	17,9	80	25,5	115	51
1L10065	3,3	22,4	74	32,0	106	64
1L10075	3,2	26,6	85	38,0	122	76
1L10303	0,6	106,8	64	152,5	92	305
(D) Sede • Housing Ø mm 12,5 (d) Spina • Rod Ø mm 6,3						
Sezione filo • Wire section 2,5 x 1,2						
1L13025	15,5	8,8	136	12,5	194	25
1L13032	12,2	11,2	137	16,0	195	32
1L13038	10,3	13,3	137	19,0	196	38
1L13045	8,7	15,4	134	22,0	191	44
1L13050	7,5	17,9	134	25,5	191	51
1L13065	5,8	22,4	130	32,0	186	64
1L13075	4,7	26,6	125	38,0	179	76
1L13090	4,1	31,2	128	44,5	182	89
1L13101	3,6	35,7	129	51,0	184	102
1L13303	1,2	106,8	128	152,5	183	305
(D) Sede • Housing Ø mm 16 (d) Spina • Rod Ø mm 8						
Sezione filo • Wire section 3,4 x 1,2						
1L16025	20,2	8,8	177	12,5	253	25
1L16032	14,4	11,2	161	16,0	230	32
1L16038	12,3	13,3	164	19,0	234	38
1L16045	10,6	15,4	163	22,0	233	44
1L16050	8,9	17,9	159	25,5	227	51
1L16065	7,0	22,4	157	32,0	224	64
1L16075	5,8	26,6	154	38,0	220	76
1L16090	4,8	31,2	150	44,5	214	89
1L16101	4,0	35,7	143	51,0	204	102
1L16115	3,9	40,3	157	57,5	224	115
						127
						152
1L16303	1,5	106,8	160	152,5	229	305

	R	XLL 35%		Max 50%		L₀
	R	S₁	F₁	S₂	F₂	
Codice Ctg. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 20 (d) Spina • Rod Ø mm 10						
Sezione filo • Wire section 4,0 x 1,7						
1L19025	32,1	8,8	281	12,5	401	25
1L19032	24,7	11,2	277	16,0	395	32
1L19038	20,7	13,3	275	19,0	393	38
1L19045	17,8	15,4	274	22,0	392	44
1L19050	15,3	17,9	273	25,5	390	51
1L19065	12,1	22,4	271	32,0	387	64
1L19075	10,2	26,6	271	38,0	388	76
1L19090	8,6	31,2	268	44,5	383	89
1L19101	7,5	35,7	268	51,0	383	102
1L19115	6,7	40,3	270	57,5	385	115
1L19126	6,1	44,5	271	63,5	387	127
1L19140	5,5	48,7	268	69,5	382	139
1L19151	5,1	53,2	271	76,0	388	152
1L19303	2,5	106,8	267	152,5	381	305
(D) Sede • Housing Ø mm 25 (d) Spina • Rod Ø mm 12,5						
Sezione filo • Wire section 5,4 x 2,2						
1L26025	52,7	8,8	461	12,5	659	25
1L26032	40,0	11,2	448	16,0	640	32
1L26038	33,3	13,3	443	19,0	633	38
1L26045	28,6	15,4	440	22,0	629	44
1L26050	24,7	17,9	441	25,5	630	51
1L26065	19,4	22,4	435	32,0	621	64
1L26075	16,3	26,6	434	38,0	619	76
1L26090	13,9	31,2	433	44,5	619	89
1L26101	12,1	35,7	432	51,0	617	102
1L26115	10,8	40,3	435	57,5	621	115
1L26126	9,8	44,5	436	63,5	622	127
1L26140	8,9	48,7	433	69,5	619	139
1L26151	8,1	53,2	431	76,0	616	152
1L26176	6,9	62,3	430	89,0	614	178
1L26202	6,1	71,1	433	101,5	619	203
1L26303	4,0	106,8	427	152,5	610	305

Esempio d'ordine: Codice


Order example:

Bestellbeispiel:

Extra light load
Extra leichte Last

CARICO EXTRA LEGGERO

Giu 2022



	R	XLL 35%		Max 50%		L₀
		S₁	F₁	S₂	F₂	
Codice Cltg. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 32 (d) Spina • Rod Ø mm 16						
Sezione filo • Wire section 6,4 x 2,7						
1L32038	43,8	13,3	583	19,0	832	38
1L32045	37,5	15,4	578	22,0	825	44
1L32050	32,3	17,9	577	25,5	824	51
1L32065	25,4	22,4	569	32,0	813	64
1L32075	21,3	26,6	567	38,0	809	76
1L32090	18,1	31,2	564	44,5	805	89
1L32101	15,8	35,7	564	51,0	806	102
1L32115	13,9	40,3	559	57,5	799	115
1L32126	12,6	44,5	560	63,5	800	127
1L32140	11,4	48,7	555	69,5	792	139
1L32151	10,5	53,2	559	76,0	798	152
1L32176	8,9	62,3	554	89,0	792	178
1L32202	7,8	71,1	554	101,5	792	203
1L32252	6,2	88,9	551	127,0	787	254
1L32303	5,2	106,8	555	152,5	793	305
(D) Sede • Housing Ø mm 40 (d) Spina • Rod Ø mm 20						
Sezione filo • Wire section 7,8 x 3,4						
1L38050	50,8	17,9	907	25,5	1295	51
1L38065	39,7	22,4	889	32,0	1270	64
1L38075	33,1	26,6	880	38,0	1258	76
1L38090	28,1	31,2	875	44,5	1250	89
1L38101	24,5	35,7	875	51,0	1250	102
1L38115	21,6	40,3	869	57,5	1242	115
1L38126	19,5	44,5	867	63,5	1238	127
1L38140	17,8	48,7	866	69,5	1237	139
1L38151	16,3	53,2	867	76,0	1239	152
						160
1L38176	13,8	62,3	860	89,0	1228	178
1L38202	12,1	71,1	860	101,5	1228	203
1L38252	9,7	88,9	862	127,0	1232	254
1L38303	8,0	106,8	854	152,5	1220	305

	R	XLL 35%		Max 50%		L₀
		S₁	F₁	S₂	F₂	
Codice Cltg. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 50 (d) Spina • Rod Ø mm 25						
Sezione filo • Wire section 10,7 x 4,4						
1L51065	80,2	22,4	1796	32,0	2566	64
1L51075	66,9	26,6	1780	38,0	2542	76
1L51090	56,6	31,2	1763	44,5	2519	89
1L51101	49,3	35,7	1760	51,0	2514	102
1L51115	43,5	40,3	1751	57,5	2501	115
1L51126	39,3	44,5	1747	63,5	2496	127
1L51140	35,8	48,7	1742	69,5	2488	139
1L51151	32,8	53,2	1745	76,0	2493	152
						160
1L51176	27,8	62,3	1732	89,0	2474	178
1L51202	24,2	71,1	1719	101,5	2456	203
						229
1L51252	19,2	88,9	1707	127,0	2438	254
1L51303	16,0	106,8	1708	152,5	2440	305
(D) Sede • Housing Ø mm 63 (d) Spina • Rod Ø mm 38						
Sezione filo • Wire section 11,4 x 5,1						
1L63075	57,8	26,6	1537	38,0	2196	76
1L63090	51,4	31,2	1601	44,5	2287	89
1L63101	44,4	35,7	1585	51,0	2264	102
1L63115	41,6	40,3	1674	57,5	2392	115
1L63126	33,2	44,5	1476	63,5	2108	127
1L63151	27,4	53,2	1458	76,0	2082	152
						160
1L63176	24,0	62,3	1495	89,0	2136	178
1L63202	21,0	71,1	1492	101,5	2132	203
						229
1L63252	16,4	88,9	1458	127,0	2083	254
1L63303	13,6	106,8	1452	152,5	2074	305
						315
						400

Esempio d'ordine: Codice
Order example:
Bestellbeispiel: