


	R	XLL 20%		Max 30%		L ₀
		S ₁	F ₁	S ₂	F ₂	
Codice Cltg. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 10 (d) Spina • Rod Ø mm 5						
Sezione filo • Wire section 1,8 x 1,4						
3S10025	23,0	5,0	115	7,5	173	25
3S10032	17,5	6,4	112	9,6	168	32
3S10038	14,8	7,6	112	11,4	169	38
3S10045	13,0	8,8	114	13,2	172	44
3S10050	11,2	10,2	114	15,3	171	51
3S10065	9,2	12,8	118	19,2	177	64
3S10075	7,5	15,2	114	22,8	171	76
3S10303	1,9	61,0	116	91,5	174	305
(D) Sede • Housing Ø mm 12,5 (d) Spina • Rod Ø mm 6,3						
Sezione filo • Wire section 2,4 x 2,0						
3S13025	42,1	5,0	211	7,5	316	25
3S13032	33,2	6,4	212	9,6	319	32
3S13038	29,3	7,6	223	11,4	334	38
3S13045	24,6	8,8	216	13,2	325	44
3S13050	19,6	10,2	200	15,3	300	51
3S13065	15,0	12,8	192	19,2	288	64
3S13075	13,2	15,2	201	22,8	301	76
3S13090	11,4	17,8	203	26,7	304	89
3S13101	9,4	20,4	192	30,6	288	102
3S13303	3,2	61,0	195	91,5	293	305
(D) Sede • Housing Ø mm 16 (d) Spina • Rod Ø mm 8						
Sezione filo • Wire section 3,0 x 2,4						
3S16025	75,7	5,0	379	7,5	568	25
3S16032	60,2	6,4	385	9,6	578	32
3S16038	50,8	7,6	386	11,4	579	38
3S16045	42,8	8,8	377	13,2	565	44
3S16050	37,1	10,2	378	15,3	568	51
3S16065	30,3	12,8	388	19,2	582	64
3S16075	25,8	15,2	392	22,8	588	76
3S16090	21,7	17,8	386	26,7	579	89
3S16101	18,9	20,4	386	30,6	578	102
3S16115	17,0	23,0	391	34,5	587	115
						127
						152
3S16303	6,3	61,0	384	91,5	576	305

	R	XLL 20%		Max 30%		L ₀
		S ₁	F ₁	S ₂	F ₂	
Codice Cltg. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 20 (d) Spina • Rod Ø mm 10						
Sezione filo • Wire section 4,0 x 3,2						
3S19025	216,0	5,0	1080	7,5	1620	25
3S19032	168,0	6,4	1075	9,6	1613	32
3S19038	129,0	7,6	980	11,4	1471	38
3S19045	112,0	8,8	986	13,2	1478	44
3S19050	94,0	10,2	959	15,3	1438	51
3S19065	72,1	12,8	923	19,2	1384	64
3S19075	59,7	15,2	907	22,8	1361	76
3S19090	50,5	17,8	899	26,7	1348	89
3S19101	44,2	20,4	902	30,6	1353	102
3S19115	38,4	23,0	883	34,5	1325	115
3S19126	34,1	25,4	866	38,1	1299	127
3S19140	31,0	27,8	862	41,7	1293	139
3S19151	28,2	30,4	857	45,6	1286	152
3S19303	14,0	61,0	854	91,5	1281	305
(D) Sede • Housing Ø mm 25 (d) Spina • Rod Ø mm 12,5						
Sezione filo • Wire section 5,6 x 4,1						
3S26025	375,0	5,0	1875	7,5	2813	25
3S26032	297,0	6,4	1901	9,6	2851	32
3S26038	219,0	7,6	1664	11,4	2497	38
3S26045	187,0	8,8	1646	13,2	2468	44
3S26050	156,0	10,2	1591	15,3	2387	51
3S26065	123,0	12,8	1574	19,2	2362	64
3S26075	99,0	15,2	1505	22,8	2257	76
3S26090	84,0	17,8	1495	26,7	2243	89
3S26101	73,0	20,4	1489	30,6	2234	102
3S26115	65,0	23,0	1495	34,5	2243	115
3S26126	57,7	25,4	1466	38,1	2198	127
3S26140	52,7	27,8	1465	41,7	2198	139
3S26151	47,8	30,4	1453	45,6	2180	152
3S26176	41,0	35,6	1460	53,4	2189	178
3S26202	35,8	40,6	1453	60,9	2180	203
3S26303	22,9	61,0	1397	91,5	2095	305

Esempio d'ordine: Codice
Order example:
Bestellbeispiel:



	R	XLL 20%		Max 30%		L ₀
		S ₁	F ₁	S ₂	F ₂	
Codice Clig. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 32 (d) Spina • Rod Ø mm 16						
Sezione filo • Wire section 6,9 x 5,3						
3S32038	388,0	7,6	2949	11,4	4423	38
3S32045	324,0	8,8	2851	13,2	4277	44
3S32050	272,0	10,2	2774	15,3	4162	51
3S32065	212,0	12,8	2714	19,2	4070	64
3S32075	172,0	15,2	2614	22,8	3922	76
3S32090	141,0	17,8	2510	26,7	3765	89
3S32101	122,0	20,4	2489	30,6	3733	102
3S32115	107,0	23,0	2461	34,5	3692	115
3S32126	93,0	25,4	2362	38,1	3543	127
3S32140	86,0	27,8	2391	41,7	3586	139
3S32151	78,0	30,4	2371	45,6	3557	152
3S32176	67,2	35,6	2392	53,4	3588	178
3S32202	59,1	40,6	2399	60,9	3599	203
3S32252	46,4	50,8	2357	76,2	3536	254
3S32303	38,0	61,0	2318	91,5	3477	305
(D) Sede • Housing Ø mm 40 (d) Spina • Rod Ø mm 20						
Sezione filo • Wire section 8,4 x 6,2						
3S38050	350,0	10,2	3570	15,3	5355	51
3S38065	269,0	12,8	3443	19,2	5165	64
3S38075	219,0	15,2	3329	22,8	4993	76
3S38090	190,0	17,8	3382	26,7	5073	89
3S38101	163,0	20,4	3325	30,6	4988	102
3S38115	142,0	23,0	3266	34,5	4899	115
3S38126	128,0	25,4	3251	38,1	4877	127
3S38140	115,0	27,8	3197	41,7	4796	139
3S38151	105,0	30,4	3192	45,6	4788	152
						160
3S38176	89,0	35,6	3168	53,4	4753	178
3S38202	77,0	40,6	3126	60,9	4689	203
3S38252	61,0	50,8	3099	76,2	4648	254
3S38303	51,0	61,0	3111	91,5	4667	305

	R	XLL 20%		Max 30%		L ₀
		S ₁	F ₁	S ₂	F ₂	
Codice Clig. No.	Rigidità Rate N/mm	Corsa Stroke mm	Carico Load N	Corsa Stroke mm	Carico Load N	Lungh. libera Free length mm
(D) Sede • Housing Ø mm 50 (d) Spina • Rod Ø mm 25						
Sezione filo • Wire section 11,3 x 7,4						
3S51065	413,0	12,8	5286	19,2	7930	64
3S51075	339,0	15,2	5153	22,8	7729	76
3S51090	288,0	17,8	5126	26,7	7690	89
3S51101	245,0	20,4	4998	30,6	7497	102
3S51115	215,0	23,0	4945	34,5	7418	115
3S51126	192,0	25,4	4877	38,1	7315	127
3S51140	168,0	27,8	4670	41,7	7006	139
3S51151	154,0	30,4	4682	45,6	7022	152
						160
3S51176	134,0	35,6	4770	53,4	7156	178
3S51202	117,0	40,6	4750	60,9	7125	203
						229
3S51252	89,0	50,8	4521	76,2	6782	254
3S51303	73,0	61,0	4453	91,5	6680	305
(D) Sede • Housing Ø mm 63 (d) Spina • Rod Ø mm 38						
Sezione filo • Wire section 11,2 x 12,9						
3S63075	630,0	15,2	9576	22,8	14364	76
3S63090	485,0	17,8	8633	26,7	12950	89
3S63101	434,0	20,4	8854	30,6	13280	102
3S63115	384,0	23,0	8832	34,5	13248	115
3S63126	349,0	25,4	8865	38,1	13297	127
3S63151	276,0	30,4	8390	45,6	12586	152
						160
3S63176	237,0	35,6	8437	53,4	12656	178
3S63202	210,0	40,6	8526	60,9	12789	203
						229
3S63252	165,0	50,8	8382	76,2	12573	254
3S63303	134,0	61,0	8174	91,5	12261	305
						315
						400

Esempio d'ordine: Codice
Order example:
Bestellbeispiel: